

baucoplus Access Panel

ACCESS PANEL SOLUTIONS INC.

toll-free 1-877-592-0033

www.accesspanelsolutions.com

TITLE: Custom Double Door

Gypsum Board: _____ (5/8" or 1/2")

Panel Width (W): _____ **Panel Length (L):** _____

Door Length (D1 or D2): _____ **Door Width (W):** _____

Latch: screw driver operated cam-latch _____
tamper resistant cam-latch _____
keyed lock _____ concealed touch-latch _____

Door: Aluminum extrusion, non-corrosive hardware, safety catches, installation aides, & bracing.

Frame: Recessed aluminum extrusion provides edge-bead, against which door and surrounding surface can be finished.

Hinge: Unique patented concealed non-corroding 2-point pin hinge, allows door to open to 120° & door can be removed for full access.

Finish: Frame mill finish. Gypsum board ready to be finished matching surrounding wall or ceiling surface.

Gasket: Self-adhesive draft seal enclosed.

Framing: Frame opening to width & length plus minimum of 1". Board to frame opening less 1/4", leaving a minimum edge of 7/8" surrounding the rough opening.

Installation: Pass baucoplus door with frame thru opening and lay aluminum frame onto wallboard edge around opening. Place fasteners thru board into aluminum frame.

Comments:

FILENAME:

BP DOUBLE DOOR SUBMITTAL DRAWING.VSD

